



SOLAR LIGHT POLE

mira 8000 **P400-215**

PRELIMINARY DATA SHEET

Self-sufficient and maintenance-free solar light pole with award winning, protected design, ideal for outdoor residential and municipal lighting.

Light source	10 high-efficiency LEDs
Max. LED power	123 Watt
SOP Solar Operating Power	40 Watt
Max. luminous flux @ SOP	6,450 lm
Luminaire efficacy	160 lm/W
Nominal power of solar cells	205 Watt peak
SPR System Power Ratio	10
Autonomy	3 nights (36h)
Pole height	8.0 / 10.0 / 12.0 m
Light spot height	7.75 / 9.75 / 11.75 m

© DT INTERNATIONAL SA 2019
11 Rue d'Italie, CH-1204 Geneva, Switzerland
www.dti-energies.com / info@dti-energies.com / +41 22 752 50 41

TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.
MISPRINTS RESERVED. JANUARY 2019



Tamar, Hong Kong



Vienna, Austria



Doha, Qatar

LUMINAIRE

SOP Solar Operating Power	40 Watt
Max. luminous flux @ SOP	6,450 lm
Luminaire efficacy	160 lm/W
Correlated Colour Temperature (CCT)	5,000 K (cool white) 3,000 K (warm white) - optionally 4,000 K (neutral white) - optionally
Colour rendering index (CRI)	≥ 70
Life time of LEDs (L70/B10)	> 90,000 hours
Material (housing)	Aluminium
Finishing (housing)	Powder-coated
Weight	8.5 kg

POLE, PIPE BEND

Wind class acc. EN 40	45 m/s
Pole height	8.0 / 10.0 / 12.0 m
Light spot height	7.75 / 9.75 / 11.75 m
Pole diameter	215 mm (8.0 m pole)
Pole weight	146 kg (8.0 m pole)
Boom angle	15 °
Pipe bend length	1,150 mm
Pipe bend weight	28.0 kg
Foundation	Flange plate Sleeve foundation - optionally
Material	Steel
Finishing	Hot-dip galvanized Paint-coated RAL 9006 (white aluminium) Powder-coating, other RAL colours - optionally
Corrosion class	C4

2X POWER TUBE P200-215

Technology	Silicon solar cells
Number of solar cells (array)	48 pcs (4 strings x 12 pcs / string)
Nominal power of solar cells	205 Watt peak
Dimensions (mm)	L1,997 x Ø215
Weight	17.0 kg

POWER CONTROL

Programmable microcontroller	✓
Controller location	Pole
Dynamic light profile	Customer-specific
Motion detector	Optionally
Hybrid power supply (AC back-up)	Optionally

BATTERY

Technology	VRLA, cycle type
Location	earth pit
Capacity	120 Ah / 12 V
Dimensions (mm)	L407 x W177 x H225
Weight	35.0 kg

SYSTEM

SPR System Power Ratio	10
Autonomy	3 nights (36h)

STANDARDS AND COMPLIANCES

ISO	ISO 9001-2015
Illumination	According to EN 13201, IESNA RP-8-00
Light pole	EN 40
Power tube impact protection rating	IK06
Photovoltaics	EN 61215 (adapted)
Temperature range	-40 °C to +50 °C (battery in earth pit)
CE	✓
RoHS	✓