



SOLAR LIGHT POLE

antares 4000 P100-160

PRELIMINARY DATA SHEET

A self-sufficient, maintenance-free solar light pole for professional outdoor lighting applications such as residential areas.

Light source	6 high-efficiency LEDs
Max. LED power	75 Watt
SOP Solar Operating Power	20 Watt
Max. luminous flux @ SOP	3,150 lm
Luminaire efficacy	160 lm/W
Nominal power of solar cells	115 Watt peak
SPR System Power Ratio	5
Autonomy	3 nights (36h)
Pole height	4.0 / 5.0 / 6.0 m
Light spot height	4.1 / 5.1 / 6.1 m

© DT INTERNATIONAL SA 2019
11 Rue d'Italie, CH-1204 Geneva, Switzerland
www.dti-energies.com / info@dti-energies.com / +41 22 752 50 41

TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.
MISPRINTS RESERVED. JANUARY 2019



Al Noof Kindergarten, Sharjah, U.A.E.



Al Amal Hospital, Dubai, U.A.E.



Varazdinske Toplice, Croatia

LUMINAIRE

SOP Solar Operating Power	20 Watt
Max. luminous flux @ SOP	3,150 lm
Luminaire efficacy	160 lm/W
Correlated Colour Temperature (CCT)	5,000 K (cool white) 3,000 K (warm white) - optionally 4,000 K (neutral white) - optionally
Colour rendering index (CRI)	≥ 70 ≥ 80 - optionally
Life time of LEDs (L70/B10)	> 90,000 hours
Material (housing)	Aluminium
Finishing (housing)	Powder-coated
Weight	3.3 kg

POLE, BRACKET

Wind class acc. EN 40	45 m/s
Pole height	4.0 / 5.0 / 6.0 m
Light spot height	4.1 / 5.1 / 6.1 m
Pole diameter	102 mm (4.0 m pole)
Pole weight	55 kg (4.0 m pole)
Boom angle	0 °
Bracket length	1,500 mm
Bracket weight	8.0 kg
Foundation	Flange plate Sleeve foundation - optionally
Material	Steel
Finishing	Hot-dip galvanized Paint or powder-coating in RAL colours - optionally
Corrosion class	C4
Other pole heights, bracket lengths and boom angles optionally.	

POWER TUBE P100-160

Technology	Silicon solar cells
Number of solar cells (array)	27 pcs (3 strings x 9 pcs / string)
Nominal power of solar cells	115 Watt peak
Dimensions (mm)	L1,520 x Ø160
Weight	7.0 kg

POWER CONTROL

Programmable microcontroller	✓
Controller location	Luminaire
Dynamic light profile	Customer-specific
Motion detector	Optionally
Hybrid power supply (AC back-up)	Optionally

BATTERY

Technology	VRLA, cycle type
Location	earth pit
Capacity	60 Ah / 12 V
Dimensions (mm)	L260 x W160 x H178
Weight	20.0 kg

SYSTEM

SPR System Power Ratio	5
Autonomy	3 nights (36h)

STANDARDS AND COMPLIANCES

ISO	ISO 9001-2015
Illumination	According to EN 13201, IESNA RP-8-00
Light pole	EN 40
Power tube impact protection rating	IK06
Photovoltaics	EN 61215 (adapted)
Temperature range	-40 °C to +50 °C (battery in earth pit)
CE	✓
RoHS	✓